

Specifikációk

AR30

R32



		Indoor Unit		AR09TXHQBWKNEU	AR12TXHQBWKNEU
		Outdoor Unit		AR09TXHQBWKXEU	AR12TXHQBWKNEU
Performance	Capacity (kW)	Cooling		2.638	3.517
		Heating		2.931	3.810
		Cooling (Min - Max)		0.91 - 3.40	1.11 - 4.16
		Heating (Min - Max)		0.82 - 3.37	1.08 - 4.22
	EER/COP (W/W)	EER (Cooling)		3.43	2.90
		COP (Heating)		3.91	3.50
	SEER/SCOP (W/W)	SEER (Cooling)		6.30	6.10
		SCOP (Heating-AVERAGE)		4.00	3.90
		SCOP (Heating-WARMER)		4.60	4.60
	Energy Grade	Star/Ticks/Level		A++ / A+	A++ / A
		SCOP WARMER Level		A++	A+
	Air Circulation (Max, m ³ /hr)			7.8	9.0
Moisture Removal (l/hr)			1.0	1.2	
Noise Level	Catalogue	Indoor High/Low	55	55	
Power		Outdoor High	62	65	
Noise Level	Catalogue	Indoor High/Low	36 / 20	37 / 22	
Pressure		Outdoor High	49	50	
Electrical Data	Energy	Operating Current (Cooling, A)		3.30	5.27
	Efficiency	Power Consumption (Cooling, W)		770	1,213
	Power Source	V/Hz/Φ		220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Physical Specification	Dimension	Net Dimension	Indoor	805x285x194	805x285x194
		(WxHxD)	Outdoor	720x495x270	720x495x270
		Gross Dimension	Indoor	880x360xx285	880x360xx285
		(WxHxD)	Outdoor	835x540x300	835x540x300
	Weight(kg)	Net Weight	Indoor	8.1	8.1
		(kg)	Outdoor	23.2	23.2
		Gross Weight	Indoor	11.5	11.5
		(kg)	Outdoor	25.5	25.5
Loading Q'ty	W/O Pipe	Set (20/40ft/40ft HC)		126/270/300	126/270/300
Technical Information	Piping Length	Piping Length (Max, m)		25	25
	Piping Height	Piping Height (Max, m)		10	10
	Refrigerant Type			R32	R32
	SVC Valve	Liquid (OD)		6.35	6.35
Gas (OD)			9.52	9.52	

Specifikációk

AR30

R32



		Indoor Unit	AR09TXHQBWKNEU	AR12TXHQBWKNEU
		Outdoor Unit	AR09TXHQBWKXEU	AR12TXHQBWKNEU
General Feature	Air Flow	Triangle Technology	-	-
	Air Direction Control (Up/Down)		Auto	Auto
	Air Direction Control (Left/Right)		Manual	Manual
	Air Flow Control Step (Cool/Fan)		3 / 3	3 / 3
	Auto Fan speed		●	●
Air Purification	Rectangle	3-CARE Filter	-	-
		PRE-FILTER	●	●
		Auto Clean (Self Cleaning)	-	-
Convenience	Smart wifi		-	-
	Indoor Temp. Display		●	●
	Remote Controller		●	●
	Remote Controller Holder		●	●
	Display On/Off	88 Display	●	●
		3 LED Display	-	-
	Beep On/Off		●	●
	24-Hour Timer / Real Timer		24-Hour Timer	24-Hour Timer
	Auto Changeover		-	-
	Auto Restart		●	●
Low Ambient Operating Mode	Condition	T1	T1	
	Cooling (°C)	-10~46°C	-10~46°C	
	Fast Cool	●	●	
	Comfort Cool	-	-	
	Dlight Cool	-	-	
	Good Sleep	●	●	
	Dehumidification	●	●	
	Auto Mode	●	●	
	Fan Mode	●	●	
	Quiet	-	-	