

Specifikációk

Wind-Free™ Elite



Indoor Unit		AR09TXCAAWKNEU	AR12TXCAAWKNEU		
Outdoor Unit		AR09TXCAAWKXEU	AR12TXCAAWKXEU		
Capacity	Capacity (kW)	Cooling	2.50	3.50	
		Heating	3.20	4.00	
	Cooling (Min - Max)	Cooling (Min - Max)	0.9 - 3.6	0.9 - 4.8	
		Heating (Min - Max)	0.8 - 7.1	0.8 - 7.3	
	EER/COP (W/W)	EER (Cooling)	4.63	3.95	
		COP (Heating)	4.74	4.26	
	SEER/SCOP (W/W)	SEER (Cooling)	8.80	8.50	
		SCOP (Heating)	5.10	5.10	
	Energy Grade	Star/Ticks/Level	A+++ / A+++	A+++ / A+++	
	Air Circulation (Max, m ³ /min)		11.1	12.1	
	Moisture Removal (l/hr)		1.00	1.5	
	Noise Level (Power)	Catalogue	Indoor High/Low	56	58
			Outdoor High	59	62
	Noise Level (Pressure)	Catalogue	Indoor High/Low	39 / 16	40 / 16
Outdoor High			45	46	
Electrical Data	Energy Efficiency	Operating Current (Cooling)	2.9	4.1	
		Operating Current (Heating)	3.4	4.4	
	Power Source	Power Consumption (Cooling)	540	885	
		Power Consumption (Heating)	675	940	
	V/Hz/Φ	220-240V/50Hz/1P	220-240V/50Hz/1P		
Physical Specification	Dimension (WxHxD)	Net Dimension Indoor	889x299x215	889x299x215	
		Outdoor	790x548x285	790x548x285	
		Gross Indoor	950x290x375	950x290x375	
		Outdoor	913x622x371	913x622x371	
	Weight(kg)	Net Weight Indoor	10.6	10.6	
		Outdoor	32.5	32.5	
		Gross Weight Indoor	12.7	12.7	
		Outdoor	34.8	34.8	
Loading Q'ty	W Pipe	Set (20/40ft/40ft HC)	-	-	
		Set (20/40ft/40ft HC)	85 / 180 / 208	85 / 180 / 208	
	W/O Pipe	Indoor (20/40ft/40ft HC)	288 / 592 / 660	288 / 592 / 660	
		Outdoor (20/40ft/40ft HC)	111 / 234 / 312	111 / 234 / 312	
Technical Information	Piping Length	Piping Length (Max, m)	15	15	
		Piping Height	8	8	
	Refrigerant	Type	R32	R32	
		Charging (kg)	0.965	0.965	
		Charging (tCO ₂ e)	0.65	0.65	
	SVC Valve	Liquid (OD)	6.35	6.35	
		Gas (OD)	9.52	9.52	

Specifikációk

Wind-Free™ Elite



		Indoor Unit	AR09TXCAAWKNEU	AR12TXCAAWKNEU	
		Outdoor Unit	AR09TXCAAWKXEU	AR12TXCAAWKXEU	
General Feature	Air Flow	Wind-Free	•	•	
		Air Direction Control (Up/Down)	Auto	Auto	
Air Direction Control (Left/Right)		Auto	Auto		
Air Flow Control Step (Cool/Fan)		5/4	5/4		
		Auto Fan speed	•	•	
	Air	Easy Filter Plus	•	•	
Purification		Tri-care Filter	•	•	
		Auto Clean (Self Cleaning)	•	•	
Convenience	Smart Things	MDS (Motion Detect Sensor)	•	•	
		Filter Cleaning Indicator	•	•	
		Indoor Temp. Display	•	•	
		Remote Controller	•	•	
		Display On/Off 88 Display	•	•	
		Beep On/Off	•	•	
		24-Hour Timer / Real Timer	24 Hr	24 Hr	
		Auto Changeover	•	•	
		Auto Restart	•	•	
			Condition	T1	T1
Low Ambient		Cooling (°C)	-10~46	-10~46	
		Heating (°C)	-15~24	-15~24	
Operating Mode	Comfort	AI AUTO & WIFI & MDS	•	•	
		AI AUTO & Auto Mode	NO	NO	
		Fast Cool	•	•	
		Good Sleep	•	•	
		Eco mode	•	•	
		Dehumidification	•	•	
		Fan Mode	•	•	
		Quiet	•	•	
	Outdoor Unit & PBA	Compressor Type	Anti-Corrosion Fin	•	•
			Compressor	•	•
PBA Protector			•	•	
Window Display	DISPLAY TYPE		88	88	
	LED Spec	LED 3ea	AI/Timer/WIFI	NO	
			AI/Timer/WIFI	•	
			Saving/Timer	NO	
	Operating/Saving	NO	NO		
MDS	MDS Icon	•	•		